



READY TO USE



OPTIMIZED INTERNAL TEMPERATURE



COMPACT SIZE



EXCELLENT VALUE FOR MONEY



5 POWER SIZES AVAILABLE

SOFTWARE

ViewPower is an advanced software that allows to manage the UPS directly by PC.

All main information and UPS parameters are available at a glance, and they can be quickly setup through few simple clicks.



| MODEL | PL-650 | PL-850 | PL-1000 | PL-1500 | PL-2000 |
|-----------------------------------|--|----------------|---|-----------------|------------------|
| Power | 650 VA / 360 W | 850 VA / 480 W | 1000 VA / 600 W | 1500 VA / 900 W | 2000 VA / 1200 W |
| MAIN INPUT | | | | | |
| Rated voltage | 220/230/240 VAC | | | | |
| Voltage range | 162~290 VAC | | | | |
| Frequency range | 50/60 Hz (auto sensing) | | | | |
| OUTPUT | | | | | |
| Voltage regulation (battery mode) | ±10% | | | | |
| Frequency range (battery mode) | 50/60 Hz ±1 Hz | | | | |
| Transfer time | 2-6 ms | | | | |
| Power factor | 0.6 | | | | |
| Wave form | Simulated sinewave | | | | |
| BATTERIES | | | | | |
| Battery type | Pb | | | | |
| Battery capacity | 12 V / 7 Ah | 12 V / 9 Ah | 12 V / 7 Ah | 12 V / 9 Ah | 12 V / 9 Ah |
| Number of batteries | 1 | 1 | 2 | 2 | 2 |
| Backup time (PC + Monitor) | 12 minutes | 22 minutes | 50 minutes | 60 minutes | 70 minutes |
| Recharge time | 4-6 h to recover 90% capacity | | | | |
| SYSTEM | | | | | |
| Protections | Overload, discharge, and overcharge protection | | | | |
| Indicators | AC Mode: Green led lighting Battery Mode: Green led flashing Fault: Turned off led | | AC Mode: Green led lighting Battery Mode: Yellow led lighting Fault: Red led lighting | | |
| Alarm | Battery Mode: sounding every 10 seconds Low battery: sounding every second Overload: sounding every 0.5 second Fault: continuous sounding | | | | |
| Interface | USB / RJ11 | | USB / RJ11 / RJ45 | | |
| Supported Operating System | Windows, MacOS, Linux | | | | |
| ENVIRONMENT | | | | | |
| Operating temperature | 0 ~ 40°C | | | | |
| Relative humidity | 0 ~ 90% (no condensing) | | | | |
| Noise (dBA at 1 meter far) | < 40 | | | | |
| MECHANICAL DATA | | | | | |
| Outlet | 4 x IEC | | | 6 x IEC | |
| Dimensions W*D*H (mm) | 101*279*142 | | 130*320*182 | | |
| Weight (Kg) | 4.2 | 4.9 | 8.2 | 10.4 | 11 |